



WORK® specially cares the quality of automatic brake winches. It has been designed according to the VGB 8/10.93 norm.



This lifter includes the new internal pendular system IPS (patent pending) of WORK®, which blocks profiles between themselves for maximum security.



The powerful auto-blocking bolts have been oversized to hold heavy loads during lifting operation.



Its fixation system provides a safe and easy installation of the Line Array speaker.



Diagonal bar behind the lifting tower provides additional reinforcement to bear lifter pressure load.



Distance between legs for a better stability.

Perfectly suitable for subwoofer location.



This accessory, included with the WT 600, allows a safe lifting of the Line Array.

Two colours available:



WT 600



WT 600 B



The ultimate reference for Line array lifting.

Based on the 400 series engineering, WORK® presents the WT 600, a top quality lifter specially designed for Line Array systems. To support heavy Line Array systems, the loudspeaker bracket has been strengthened, taking into account strain exerted by the loudspeaker. A light inclination angle at the opposite part of the load provides a perfect stability of the lifter and its load, respecting the centre of gravity. Metal wall thickness and subsection rings ensure the right distribution of the weight on the bracket.

The profile section has been improved too, with a special reinforcement on both sides that reduces strain supported by profiles when the lifter is unfolded. This is particularly adequate for large audio systems. The high quality automatic brake winch, steel made pulleys and oversized cable guarantee that fold/unfold operations will be successfully achieved.

Last but not least, position of front legs and distance between them increase lifter stability. There is enough space for the insertion of subwoofers that complete the Line Array system.

WT 600 is also available in black colour (WT 600 B).

WT 600

Lifting tower for Line Array



Load capacity and weight:

Weight:

245 kg.

Minimum load:

30 kg.

Maximum load:

350 kg.

Min. and max. height:

Minimum height:

1.96 m.

Maximum height:

6.50 m.

Dimensions:

Unfolded base dimensions:

2.51 x 2.15 m.

Folded base dimensions:

0.75 x 0.74 m.



Accessories

Line Array adapter: reinforcement bar for a safe lifting of heavy Line Array systems. See more details about our accessories pg. 36-37.



Cable and winch

Cable:

Composition: 6 x 19+1.
Diameter: 7 mm.
Resistance: 1770 N / mm2.

Winch:

Drum diameter capacity:
Reduction range: 10.5 : 1:



Features

- Four extensible profiles made of extruded aluminium.
- Exclusively designed for heaviest Line Array systems.
- Internal safety pendular system (IPS).
- Diagonal bar behind the lifting tower for additional reinforcement.
- Four wheels at the base of the lifter for transport.
- Colour available: Silver metal and black.



Norms / Certificates

Lifter:

CE • BGV C1

Winch:

VGB 8/10.93;
89/392/EWG;
98/37/EG.