



WT 150

Lifting tower for Line Array

Load capacity and weight:

Weight:
70 kg (154.3 lb)
Minimum load:
30 kg (66.14 lb)
Maximum load:
200 kg (440.8 lb)

Min. and max. height:

Minimum height:
1.57 m (5.15 ft)
Maximum height:
5 m (16.4 ft)

Dimensions:

Unfolded base dimensions:
2.18 x 1.75 m
(7.15 x 5.74 ft)
Folded base dimensions:
0.51 x 0.48 m
(1.67 x 1.57 ft)

WT 150, the most compact lifting tower of the market for Line Array systems.

WT 150 is without a doubt the most compact lifting tower of the market for Line Array systems. It fits in almost any car, because it only measures 157 cm long when it is folded. It allows installing small size Line Array systems with maximum convenience.


Like the other lifters exclusively designed for Line Array systems, WT 150 gives users the assurance that they are working with a top quality lifting tower, which protects people and loads (up to 200 kg).

Dual reinforcing bars at the back of the tower help to withstand the weight of the load during operation.

Two colours available:



WT 150



WT 150 B



WT 150 perfectly fits in commercial vehicles. It only measures 157 cm long when it is folded.



Powerful oversized locking bolts designed to support heavier loads with ease during lifting operations. New patented steel profile cap designed for added rigidity to the tower.



WORK® cares particularly for the quality of automatic brake winches. They have been designed according to the norms 2006/43 EG, EN 13157 and EN 12100.




WT 150 has been designed for line array systems, that is why it includes a frontal reinforcement for the bracket.



Dual reinforcing bars at the back of the tower help to withstand the weight of the load during operation.




Distance between legs gives the lifter a better stability.



It also provides a space suitable for subwoofer location.



Truss adapter, useful to lift any truss shape (triangle, square, etc.).
More details about accessories pg. 40-41.



Cable and winch

Cable:
Composition: 6 x 19+1.
Diameter: 6 mm.
Resistance: 1770 N / mm².
Winch:
Drum diameter capacity: 48 mm.
Reduction range: 10.5 : 1.



Features

- Four extensible profiles made of extruded aluminium.
- Exclusively designed for small/medium size Line Array systems.
- Dual reinforcing bars on the back of the lifter for additional reinforcement.
- Castors at the base of the lifter.
- Available colour: Silver metal and black.



Norms / Certifications

Lifter:

CE · BGVC1

Winch:

- 2006/43 EG.
- EN 13157.
- EN 12100.