



Additional wheels for its transport in horizontal position.



High resistance stabilizer legs with rubber made base.



For more convenience during transport, stabilizer legs are put in the space provided.



The base of LW 290 R has an additional stabilizer that makes lifting operation safer, due to the heavy loads this lifter holds (290 kg at 6.6 meters high).



Pulley system and safety pin on each section. Vertex with reinforcement.



LW 255 R, LW 265 R and LW 290 R feature a strong, high quality automatic brake winch that allows heavy load lifting. It has been designed according to the VGB 8/10.93 norm.

The most complete telescopic lifter of WORKiW®.


LW 290 R features are impressive: thanks to its five extensible steel profiles, it holds 290 kg loads and lifts them at 6.6 meters, using a high traction resistant cable. A pulley with auto-lubricated bearing system guides the cable for a correct use of the lifter. All the mobile system is fixed with safety fastener locks that are necessary during the tower strain.

LW 290 R features adjustable stabilizers on its legs for a perfect stability in all kind of surface, including a bubble level to balance it. An additional stabilizer has been placed at the centre of the tower, taking into account that this lifter holds heavy loads. The latter are better distributed between base and legs.

Four wheels ensure an easy use and transport, whereas others on the mast make possible its transport in horizontal position.

The tower has been dunked into a melting bath of zinc for a durable protection against corrosion and oxidation.

LW 290 R is available in two colours: silver metal and black (LW 290 R B).



LW 290 R
Telescopic lifter

Load capacity and weight:


Weight:
184 kg.
Minimum load:
25 kg.
Maximum load:
290 kg.

Min. and max. height:

Minimum height:
1.84 m.
Maximum height:
6.60 m.

Dimensions:

Diameter:
50 mm.
Unfolded base dimensions:
1.79 x 1.79 m.
Folded base dimensions:
0.46 x 0.46 m.



Accessories

AW 150 / AW 250 / AW 350 / AW 550 / AW 450 / AW 30 / AW 29.

See more details about our accessories pg. 36-37.



Cable and winch

Cable:
Composition: 7 x 19.
Diameter: 7 mm.
Resistance: 1770 N / mm².
Winch:
Drum diameter capacity: 48 mm.
Reduction range: 3.75 : 1.



Features

- Five extensible steel profiles.
- Additional stabilizer on the center of the tower for an optimum distribution of the load.
- Four wheels at the base of the lifter + handle for a convenient transport.
- Dunked into a melting bath of zinc for a durable protection against corrosion and oxidation.
- 50 mm diameter / suitable with many accessories.
- Colour available: Silver metal and black.



Norms / Certificates

Lifter:
CE • BGV C1
Winch:
VGB 8/10.93;
89/392/EWG;
98/37/EG.