



# LW 185 R

Telescopic lifter

## Weight and load capacity:


**Weight:**  
73.2 kg.  
**Minimum load:**  
20 kg.  
**Maximum load:**  
210 kg.

## Min. and max. height:

**Minimum height:**  
1.72 m.  
**Maximum height:**  
5.30 m.

## Dimensions:

**Diameter:**  
35 mm.  
**Unfolded base dimensions:**  
1.49 x 1.49 m.  
**Folded base dimensions:**  
0.46 x 0.46 m.



Features of this telescopic tower clearly mark the difference with previous models.

**LW 185 R** has been designed to lift up to 210 kg at 5.30 meters high, thanks to four extensible steel profiles and a high traction resistant cable (guided by pulley featuring auto-lubricated bearing). All the mobile system is fixed with safety fastener locks that are necessary during the tower strain.

**LW 185 R** features adjustable stabilizers on its legs for a perfect stability in any surfaces, including a bubble level to balance it. Four wheels below the winch ensure an easy use and transport.

The tower has been dunked into a melting bath of zinc for a durable protection against corrosion and oxidation. **LW185 R** is available in two colours: silver metal and black (LW 185 R B).

**NEW BASE (reinforced):**  
Now lifts up to 210 kg.



LW 185 R is a 4 wheel base lifter. For more convenience during transport, stabilizer legs are put in the space provided.



High resistance stabilizer legs with rubber made base.



LW 185 R features a bubble level vial, useful to balance the lifter and ensures vertical lifting, protecting load from inadvertent movements.




Pulley system and safety pin on each section. Vertex with reinforcement.



The high quality automatic brake winch has been designed according to the VGB 8/10.93 norm and TÜV 9591009 certificate.

Handle located on the body allows to transport the lifter.



## Accessories

AW 135 / AW 235 / AW 335 / AW 535 / AW 10 / AW 435.

See more details about our accessories pg. 36-37.



## Cable and winch

**Cable:**  
Composition: 6 x 19+1.  
Diameter: 6 mm.  
Resistance: 1770 N / mm<sup>2</sup>.  
**Winch:**  
Drum diameter capacity: 48 mm.  
Reduction range: 3.75 : 1.



## Features

- Five extensible steel profiles.
- Four wheels at the base of the lifter + handle for a convenient transport.
- Dunked into a melting bath of zinc for a durable protection against corrosion and oxidation.
- 35 mm diameter / suitable with many accessories.
- Colour available: Silver metal and black.



## Norms / Certificates

**Lifter:**  
**CE · BGV C1**  
**Winch:**  
VGB 8/10.93;  
98/37/EG;  
TÜV 9591009.