


# LECCOR IBZA ONE SERIES DATASHEET

## IBZA P204: Ultra-Compact Full Range Loudspeaker







#### MAIN APPLICATIONS

- Background Music in restaurants, club, airpots
- Museums and AV spaces
- Convention centres
- Sports Stadia

#### MAIN FEATURES

- Compact two-way passive system
- Weatherproof plastic
- 16  $\Omega$  nominal impedance
- Mounting accessories

### **DESCRIPTION**

The P204 is a 16 Ohm Compact Full Range weatherproof plastic Loudspeaker, designed to be used as a sound reinforcement speaker in a wide variety of audio applications.

The double high sensitivity 4" cone transducer and the 25mm silk soft dome tweeter produce 111dB spl and a wide operating frequency range of 80 Hz to 20 kHz sound quality for foreground or background music, bing voice for maximun speech clarity and intelligibility.

The enclosureincludes a special mounting bracket with an adjustable splay angle of 10° vertically. The 3 support base provide by the flat bottom surface of the cabinet, allow also the speaker to be set on a surface such as shelf.

**Frequency Response** 80 Hz - 20 kHz\* Frequency Response: Free Field 86 Hz - 16 kHz ±3 dB

SPL (1m) 111 dBspl Maximum Peak SPL 117dBspl

Transducers: Low/High Frequency Two 4" cone drivers and Ø 25mm x 1

Sensitivity (1W/1m) 92dB Dispersions (HxV) 120° x 120° Power (RMS) 80 W Power (Program) 160 W Power (Peak) 320 W Rate Impedance Input Connectors **Binding Post** NET Weight 4.5 kg (9,92 lbs)

> Dimensions 182 x 182 x 320 mm (WxDxH)

(7.17" x 7.17" x 12.6")

Construction Weatherproof plastic. Finished in Black or White Protective Grille Powder coated perforated steel with acoustically transparent reticulated foam

\*Recommended maximum operating frequency range. Response depends on loading conditions and room acoustics.



