

## NEO A series

Installation loudspeakers

The **NEO A series** is composed of three self-powered models which complete the **NEO series** for maximum convenience and flexibility. They feature a two channel D-class amplifier, bass and treble tone controls, RCA, 3.5mm mini-jack inputs and a powered output for a passive speaker (included).

Each self-powered model is supplied as a complete pair, as it comes with a passive loudspeaker and cables for connection (except for the NEO 8 A).

### Discover the new NEO 8 A.

The NEO 8 A is the latest model of the NEO A series. This powerful loudspeaker differentiates itself from the others as its amplifier is exclusively dedicated to this unit. Due to this, it doesn't come with a passive loudspeaker.

### Features

- Self powered two way loudspeakers designed for fixed installations.
- D-Class amplifier for minimal weight and heat.
- Available with black and white finish.
- Included wall-mount bracket with fast mounting system.
- Each unit comes with a passive loudspeaker (except for the NEO 8 A).



NEO 8 A

NEO 5 A

NEO 6 A



The wall-mount bracket allows quick and easy installation. Speakers are easily oriented to the optimum angle for the desired coverage.



Technical data	NEO 5 A	NEO 6 A	NEO 8 A
Type:	2 way self-powered loudspeaker.	2 way self-powered loudspeaker.	2 way self-powered loudspeaker.
Elements:	5½" woofer + 0.5" TWT.	6½" woofer + 1" TWT.	8" woofer + 1" TWT.
Amplifier power:	2 x 25 W at 4 Ω.	2 x 30 W at 4 Ω.	40 W.
Input connectors:	RCA - Mini Jack 3.5 mm / Euroblock.	RCA - Mini Jack 3.5 mm / Euroblock.	RCA - Mini Jack 3.5 mm
Input sensitivity:	1 V / 2.21 dBu.	1 V / 2.21 dBu.	1 V / 2.21 dBu.
Frequency response:	60 Hz - 20 kHz.	55 Hz - 20 kHz.	50 Hz - 20 kHz.
RAL colour code:	RAL 9003 (W) / 9004 (B).	RAL 9003 (W) / 9004 (B).	RAL 9003 (W) / 9004 (B).
Material (housing):	Polypropylene plastic.	Polypropylene plastic.	Polypropylene plastic.
Material (grille):	Aluminium.	Aluminium.	Aluminium.
Main supply:	AC 115/230 V, 60/50 Hz.	AC 115/230 V, 60/50 Hz.	AC 115/230 V, 60/50 Hz.
Dimensions (WxHxD):	171 x 244 x 166 mm.	200 x 290 x 175 mm.	260 x 370 x 240 mm.
Weight:	4.4 kg each.	5.1 kg each.	5.46 kg each.

