

TU ML series

Compression drivers

These three compression drivers made of aluminium are suitable for 100 V voltage line installations.

Each model has its own output power (from 35 to 80 W). They are suitable for the horn diffusers of the TH series, being very easy to connect.

Features

- Compression drivers for 100 V line installations.
- Up to 80 W power, depending on model.
- Suitable for the horn diffusers of the TH series.
- Easy to connect to the diffuser.

Compression drivers are suitable with any models of the TH horn diffusers.



TU 80 ML

TU 60 ML

TU 35 ML

Technical data	TU 35 ML	TU 60 ML	TU 80 ML
Type:	Compression motor.	Compression motor.	Compression motor.
Power (100 V line):	35 W (285 Ω) / 20 W (500 Ω) / 10 W (1 kΩ).	60 W (166 Ω) / 40 W (250 Ω) / 20 W (500 Ω).	80 W (125 Ω) / 50 W (200 Ω) / 35 W (285 Ω).
(*) Power (70 V Line):	17.5 W (280 Ω) / 10 W (490 Ω) / 5 W (980 Ω).	30 W (163 Ω) / 20 W (245 Ω) / 10 W (490 Ω).	40 W (122 Ω) / 25 W (196 Ω) / 17.5 W (280 Ω).
Frequency response:	200 Hz - 4 kHz.	200 Hz - 4.5 kHz.	200 Hz - 4.5 kHz.
Sensitivity (1W/1m):	96 dB.	96 dB.	96 dB.
Max. SPL.:	115 dB.	115 dB.	115 dB.
Material (housing):	Metal.	Metal.	Metal.
Dimensions:	110 x 160 mm.	110 x 160 mm.	110 x 160 mm.
Weight:	1.7 kg.	2.1 kg.	2.1 kg.

(*) The power taps indicated on the selector switch are calculated for 100V line. In the case of 70V line installation, each power tap will correspond to half the value.

