

XS 1000 Pro

Headset microphone



Electret headset microphone with omnidirectional /cardioid polar pattern.

It includes a 1.5 mm Mini-jack XLR adaptor.

XS 1010 Pro

Headset microphone



Electret headset microphone with unidirectional /cardioid polar pattern.

It includes a 1.5 mm Mini-jack XLR adaptor.

XS 1500 Pro

Headset microphone



XS 1500 Pro has an ergonomic design and a robust fixation system. It is adequate for live shows because it goes unperceived and provides total liberty of movement on stage.

This microphone is very convenient to use, thanks to its fixation system and to the arm which can be oriented in any direction. It is comfortable even for those wearing glasses. It includes a 1.5 mm Mini-jack XLR adaptor.



XS AD 1.
Mini jack 2.5 mm /
Mini XLR 3 pin.



XS AD 1.
Mini jack 2.5 mm /
Mini XLR 3 pin.



XS AD 1.
Mini jack 2.5 mm /
Mini XLR 3 pin.

Technical data	XS 1000 Pro
Polar pattern:	Omnidirectional.
Output connector:	¼" Jack.
Frequency response:	20 Hz - 20 kHz.
Impedance:	1 kΩ.
Sensitivity:	-45 dB.
Main supply:	DC 9-52 V.
Microphone diameter:	Ø 5 mm.
Cable:	Ø 2 mm / 1 m length.
Weight:	36 gr.
Accessories:	Windscreen, mini-XLR adapter.

Technical data	XS 1010 Pro
Polar pattern:	Unidirectional.
Output connector:	2.5 mm mini-jack.
Frequency response:	50 Hz - 20 kHz.
Impedance:	1 kΩ.
Sensitivity:	-45 dB.
Main supply:	DC 9-52 V.
Microphone diameter:	Ø 12 mm.
Cable:	Ø 2 mm / 1.2 m length.
Weight:	42 gr.
Accessories:	Windscreen, mini-XLR adapter.

Technical data	XS 1500 Pro
Polar pattern:	Omnidirectional
Output connector:	2.5 mm mini-jack.
Frequency response:	20 Hz - 20 kHz.
Impedance:	1 kΩ.
Sensitivity:	-42 dB.
Main supply:	DC 1.5 - 10 V.
Microphone diameter:	Ø 5 mm.
Cable:	Ø 1.4 mm / 1.20 m length.
Weight:	15 gr.
Accessories:	Windscreen, mini-XLR adapter.

XS 1550 Pro

Headset microphone



XS 1550 Pro is an improved version of the XS 1500 Pro. It has an ergonomic design and a robust fixation system, being adequate for live shows. It differentiates itself from the XS 1500 Pro as it is totally foldable and can be disassembled to protect it during transport.

It includes a transport bag and a mini-XLR adapter for different kind of connection.



XS AD 1.
Mini jack 2.5 mm /
Mini XLR 3 pin.

Technical data	XS 1550 Pro
Polar pattern:	Electret omnidirectional.
Output connector:	2.5 mm mini-jack.
Frequency response:	20 Hz - 20 kHz.
Impedance:	2 kΩ.
Sensitivity:	-45 dB.
Main supply:	DC 1.5-12 V.
Microphone diameter:	Ø 3.5 mm.
Cable:	Ø 1.4 mm / 1.2 m length.
Weight:	15 gr.
Accessories:	Windscreen, mini-XLR adapter.

XS 1400 Pro

Headset microphone



XS 1400 Pro is a convenient headset microphone with a unique point of fixation. It has an omnidirectional response, low noise level and high EMI suppression, which ensures quality frequency response. Its built-in circuit provides accurate electro-acoustic response.

Technical data	XS 1400 Pro
Polar pattern:	Electret omnidirectional.
Output connector:	Mini-XLR3.
Frequency response:	20 Hz - 20 kHz.
Impedance:	1 kΩ (±30%).
Sensitivity:	-45 dB.
Main supply:	DC 1.5-10 V.
Microphone diameter:	3 mm.
Cable:	Ø 1.5 mm x 1.2 m.
Weight:	15 g.
Accessories:	Windscreen.

XS 2000 Pro

Lavalier microphone



A 2.5 mm mini jack
/ XLR adapter.



This ultra-thin electret lavalier microphone is very convenient for live shows as it goes totally unperceived. It features a mini-XLR adapter for different kind of connection.



Technical data	XS 2000 Pro
Polar pattern:	Electret omnidirectional.
Output connector:	2.5 mm mini-jack.
Frequency response:	30 Hz - 16 kHz.
Impedance:	600 Ω.
Sensitivity:	-45 dB.
Main supply:	DC 48 V.
Microphone diameter:	Ø 8 mm.
Cable:	Ø 2 mm / 1.10 m length.
Weight:	20 gr.
Accessories:	Windscreen, mini-XLR adapter.