


SW218EB_2600: High Power Subwoofer



MAIN APPLICATIONS

- Stadium
- Dance clubs
- Theatres
- Arenas

MAIN FEATURES

- High output Subwoofer
- 2 x 18" LF long excursion Hi Power drive
- Bass reflex system
- 140 dB max SPL
- 4Ω Nominal Impedance

DESCRIPTION

The SW-218EB is a high performance loudspeaker defined by its exceptional headroom and an extended frequency response.

The SW218EB housing two linear, high-excursion 18-inch cone drivers mounted in a vented cabinet and optimally tuned port with flared ends to reduce turbulence and noise under high drive conditions.

The loudspeaker's 30Hz to 150Hz operating frequency range allow it to integrate with any Tecnaire Loudspeaker System.

The subwoofer cabinet is constructed of first grade birch plywood and has a high-quality Polyurea paint finish. The front of the subwoofer is protected by a hex-stamped, steel grille backed by an acoustically transparent foam.

Two ground runners to protect the bottom allow stacking the subwoofer in horizontal and vertical position. The subwoofer shall be connected via one 4-point speakON

Frequency Response¹
 Frequency Response: Free Field²
 Axial Sensitivity @ (1W/1m)
 Calculated SPL
 Transducers
 Dispersion
 Recommended amplifier
 Power (AES³ / Continuous)
 Rated Impedance
 Input Connexion
 NET Weight
 Dimensions

30 Hz - 150 kHz
 35 Hz - 100 Hz ±3dB
 101 dB
 138 dB cont. / 144 dB peak (With T20-44 amplifier)
 2 x 18-inch LF cone driver (4.5" VC)
 360° (Only one box. Varies with number of units and configuration)
 T10-44 / T20-44
 2600W / 5200 W
 4Ω
 IN: 1xNL4 SpeakON® LINK: 1xNL4 SpeakON®
 93,5 kg. / (199 lbs)
 1340 x 700 x 561 mm / (52.7" x 27.55" x 22") (W x D x H)

Construction
 Protective Grille
 Fittings

18mm plywood. Finished in black semi-matt textured Polyurea weatherizad coating
 Powder coated perforated steel with acoustically transparent reticulated foam
 Protective soft cover and transport dolly

¹ Recommended maximum operating frequency range. Response depends on loading conditions and room acoustics.
² Free field measured with 1/3 octave frequency resolution at 4m
³ Based on AES Standard, 2 hours test applying 6dB crest factor pink noise signal withing the range Fs-10Fs (AES-1984)



Pº Ind. Monte Boyal, C/Encinar 282
 45950 Casarrubios del Monte (Toledo), SPAIN.
 Phone: +34 918 170 110
 Fax: +34 918 183 053
 www.tecnaire.com
 sales@tecnaire.com