





**IBZA 12: Compact Multi-purpose Loudspeaker**



**MAIN APPLICATIONS**

- Highly intelligible vocal reproduction
- Near-field applications
- Stand alone system
- Fixed Installations
- Main FOH or additional reinforcement

**MAIN FEATURES**

- Compact two-way passive system
- 12" - LF / 1 x 1" HF compression driver
- 8 Ω nominal impedance
- Mounting accessories

**DESCRIPTION**

The IBZA12 is a trapezoidal compact full-range loudspeaker high performance, wide-bandwidth system in a compact and efficient package. Extended frequency response is provided by a bass reflex tuned 12" low frequency driver and high frequency 1" compression driver mounted on an asymmetrical rotatable horn.

The two-way system is designed for applications where high output is required with a moderate amount of low frequency energy from a compact enclosure. It has been designed for use as stand-alone full-range speaker or together with a sub woofer (E.G. SW115 or SW118M).

The box houses multiple internal rigging points for ground-support, truss and wall mounting, screw for an external pole mount socket, and speakON® connectors.

The cabinet has been made with the latest techniques ensuring a perfect and rigid constructions. Weatherized finish is provided, as the enclosure is coated with rugged Poliurea texture finish and protected with special grills.

The system is available in both passive (IBZA12) and active (bi-amped) versión (IBZA12-PCC Box)

<b>Frequency Response<sup>1</sup></b>	56 Hz - 20 kHz ± 3dB
<b>Frequency Response: Free Field<sup>2</sup></b>	66 Hz - 18 kHz ±3 dB
<b>Axial Sensitivity @ (1w/1m)</b>	96 dB SPL
<b>Calculated SPL</b>	124 dB continuous / 130 dB peak
<b>Transducers: Low/High Frequency Dispersions (HxV)</b>	1 x 12 " LF cone driver and 1 x 1" HF driver on a asymmetric rotatable horn (50°-100°) x 60°
<b>Recommended amplifier</b>	PA2100/PA4.1500/T6-44
<b>Power<sup>3</sup></b>	600 W (AES) / 1200W continuous
<b>Rate Impedance</b>	8 Ω
<b>Input Connectors</b>	IN: 1xNL4 SpeakON® LINK: 1 X NL4 SpeakON®
<b>NET Weight</b>	19 kg (41,89 lbs)
<b>Dimensions (HxWxD)</b>	606 x 366 x 384,5 mm (23.85" x 14.40" x 15.14")
<b>Construction</b>	16mm birch plywood. Finished in black semi-matt textured Polyurea weatherized coating.
<b>Protective Grille</b>	Powder coated perforated steel with acoustically transparent reticulated fabric

<sup>1</sup> Recommended maximum operating frequency range. Response depends on loading conditions and room acoustics.  
<sup>2</sup> Free field measured with 1/3 octave frequency resolution at 4m  
<sup>3</sup> Based on AES Standard, 2 hours test applying 6dB crest factor pink noise signal withing the range Fs-10Fs (AES-1984)



Pº Ind. Monte Boyal, C/Encinar 282  
 45950 Casarrubios del Monte (Toledo), SPAIN.  
 Phone: +34 918 170 110  
 Fax: +34 918 183 053  
 www.tecnaire.com  
 sales@tecnaire.com