




## IBZA 6: Ultra-Compact Full Range Loudspeaker



### MAIN APPLICATIONS

- Background Music in restaurants, club, airports
- Museums and AV spaces
- Convention centres
- Hotels
- Distributed, Fill and Bajo Balcony

The **IBZA6** is a small trapezoidal compact full-range loudspeaker of studio sound quality, designed to be used in wide variety of audio applications as small sound reinforcement unit. The enclosure design allows for installation very close to walls and ceilings making it an ideal choice for short throw applications like distributed, under balcony or wall mounting.

### MAIN FEATURES

- Compact two-way passive system
- 6 1/2"-LF/ 1 x 1.25" Dome tweeter
- 8 Ω nominal impedance
- Mounting accessories

The **IBZA6+** is a versatile two-way passive system with a 6 1/2" low-mid frequency driver in a bass-reflex tuned enclosure and a dome tweeter. The combination provide a natural and transparent sound.

The **IBZA6** has been designed for use as stand-alone speaker or extended frequency response down with a passive sub-woofer like SW12 or SW115.

The box houses multiple internal rigging points standard M6 insert for different flying bracket.

The cabinet is coated with rugged Poliurea texture finish and protected with special grills.

Frequency Response	82 Hz - 20 kHz*
Frequency Response: Free Field	95 Hz - 18 kHz ±3 dB
SPL (1m)	114 dB SPL
Maximum Peak SPL	120 dB SPL
Transducers: Low/High Frequency	1 x 6 1/2" cone drivers and 1 x 1.25" dome tweeter
Sensitivity (1W/1m)	93dB
Dispersions (HxV)	80° x 80°
Recommended amplifier	PA900/PA4.450/T6-44
Power (Nominal)	160 W
Power (Peak)	320 W
Rate Impedance	8 Ω
Input Connectors	IN: 1xNL4 SpeakON® LINK: 1 X NL4 SpeakON®
NET Weight	4,5 kg (14,10 lbs)
Dimensions	330 x 210 x 207 mm (HxWxD) (12.99" x 8.26" x 8.15")
Construction	12mm birch plywood. Finished in black semi-matt textured Polyurea weatherized coating.
Protective Grille	Powder coated perforated steel with acoustically transparent reticulated foam

\*Recommended maximum operating frequency range. Response depends on loading conditions and room acoustics.



Pº Ind. Monte Boyal, C/Encinar 282  
45950 Casarrubios del Monte (Toledo), SPAIN.  
Phone: +34 918 170 110  
Fax: +34 918 183 053  
www.tecnaire.com  
sales@tecnaire.com