The PA 190 USB/R and PA 240 USB/R are powerful installed sound power amplifiers which deliver 180 W and 240 W output power. They can supply up to 4 different zones thanks to their front panel zone select buttons.

They both include a solid state audio player/recorder (USB/SD) compatible with standard formats (MP3, WMA). It is possible to record speechs and save them in a USB storage device. They support USB and SD storage devices with up to 32 GB memory.

Regarding audio control, their 5 input mixer (4 selectable Mic/Line, 1 Aux/CD/Tuner/Tape) includes all the functions required for full control: independent volume control, master control of level, bass and treble tone. The mixer also has a pre-out to send mixed signal to an external amplified system or to connect external devices like equalizers and processors.

Designed for installed sound system installations, they are suitable for low impedance speakers (4, 8 and 16 Ω) and high voltage lines (25/70/100 V). A monitor output is suitable for connecting up to 1W of load such as a control room monitor speaker. In addition, for maximum safety in the whole installation, it includes a Chime On/Off switch and a Telephone/Emergency connection for announcements.



PA 190 USB/R

PA 240 USB/R



Features

- Installed sound power amplifiers + 5 input mixer with 4 selectable zones.
- Solid state audio player/recorder (USB/SD) with standard formats (MP3, WMA).
- Support storage devices with up to 32 GB.
- 4 Mic inputs + 4 Line inputs.
- 1 Aux/CD/Tuner/Tape input.
- Monitor output.
- Mixer with independent control of volume, Master control and treble/bass tone.
- Pre-out function.
- Suitable with low impedance speakers (4, 8 and 16 $\Omega)$ and high impedance (25/70/100 V).
- Chime On/Off switch.
- Telephone/Emergency connection for announcements.
- 2 HU rack enclosures.

Rear panels

PA 190 USB/R / PA 240 USB/R

